# DIVAR IP 2000

www.boschsecurity.com







- u Fully featured video recording solution for up to 16 channels
- u Out-of-the-box IP video recording solution with up to 8 TB (4 x 2 TB) storage capacity
- u Robust, secure operation —instant real time access to video
- u Instantly find what you are looking for
- Remote viewing via Video Security App and Video Client by Bosch

DIVAR IP 2000 is an affordable, easy to use all-in-one recording solution for network surveillance systems of up to 16 channels (all channels pre-licensed). Running the full Bosch recording solution including the Video Streaming Gateway to integrate 3<sup>rd</sup> party cameras, DIVAR IP 2000 is an intelligent IP storage device that provides both, a professional video recording solution and ease of operation. DIVAR IP 2000 is a 4-bay mini tower unit that combines advanced management and state-of-the-art recording management into a single cost-effective, plug and play IP recording appliance for IT-minded customers which are seeking for a state-of-the-art "second generation" NVR recording solution.

### System overview

DIVAR IP 2000 utilizes a highly energy efficient, embedded design at a very affordable price which nevertheless boasts Bosch quality through-and-through.

Easy to install and operate, the DIVAR IP 2000 system features wizard-based set-up and centralized configuration to reduce installation times by as much as 45%. All components are pre-installed and pre-

configured. Simply connect to the network and power the unit up —DIVAR IP 2000 is ready to begin recording straight out-of-the-box.

#### **Functions**

DIVAR IP 2000 features front-swappable SATA-II hard drives providing up to 8 TB of gross storage capacity. All system software is pre-installed and pre-activated — creating an out-of-the-box ready-to-use video recording appliance. The DIVAR IP 2000 system utilizes Microsoft Windows Storage Server 2008 R2 (64-bit).

Remote viewing and configuration DIVAR IP 2000 is designed for remote operation and web based configuration —no need to plug in any peripherals. A standard PC or tablet computer can be used to set up the system in a few guided steps via the web based configuration wizard. Video Security App and Video Client offer advanced playback and live viewing capabilities for all video devices connected to the DIVAR IP 2000 system.

Instant real time access to video View high quality HD video despite low or limited bandwidth connections. Dynamic Transcoding technology ensures you can view your video immediately —anytime, anywhere.

Dynamic Transcoding retrieves the data from DIVAR IP 2000 and subsequently decodes and decompresses the data stream to a lower rate bit stream tailored to the bandwidth of the connection. When the video is paused, the instant detail enhancement feature instantly displays the full HD video.

Reliable storage and operation

For constant monitoring and management the operating system is always running redundantly. This way the user can be sure to be alerted in case an error such as a hard drive failure appears. Critical health states can be received as an email notification and monitored via the web based dashboard. Disk failures can easily be handled with a few guided configuration steps. The web based configuration wizard provides an option for redundant storage of the recorded video data.

#### Bosch quality

Bosch subjects all its products to the most comprehensive and rigorous battery of quality endurance tests in the industry. Our recording products are subjected to extreme temperatures, voltages and vibrations to determine true operating limits, so you can be assured of long-term reliable operation. And Bosch firmly stands behind every product it sells with an end-to-end 3 year warranty backed by technical support.

#### Certifications and approvals

Region	Certification	
Europe	Œ	DIVARIP2000/3000
USA	UL	DIVARIP2000/3000

## Installation/configuration notes

DIVAR IP 2000 comes pre-configured in a standard non-RAID configuration and provides the following specifications:

Gross capacity	Net capacity	Bandwidth (read & write)	Cameras
w/o HDD	n/a	100 Mbit/s	16
2x2TB	3524 GB	100 Mbit/s	16
4x2TB	7248 GB	100 Mbit/s	16

These values refer to the Bosch recording applications; net capacity for a non-RAID configuration; 16 connected cameras indicate the number of concurrent recordable cameras including the connected replay clients.

DIVAR IP 2000 allows a maximum of overall 16 channels: recording and replay clients.

The hard drives can optionally be configured in RAID1 mode to provide redundant storage of the video data. In this case the following specifications are valid:

Gross capacity	Net capacity	Bandwidth (read & write)	Cameras
2x2TB	1762 GB	70 Mbit/s	16
4x2TB	3624 GB	70 Mbit/s	16

The storage capacity of a DIVAR IP 2000 system can be increased by mounting additional hard drives. The following configurations are possible: 2 x 2 TB, 4 x 2 TB, 2 x 3 TB and 4 x 3 TB



#### Notice

Bosch is not liable for system failures of units equipped with non-Bosch hard drives if the non-Bosch hard drives are source of the issues.

boscii naid drives are source of the issues.			
Parts included			
Processor			
Processor	Intel Atom D525 processor + Intel ICH9R storage controller		
Socket	1		
Chipset	Intel 82801IRI/O controller hub (ICH9R) (Southbridge)		
Memory			
Memory type	DDR3 SO-DIMM		
Max front side bus	1333 MHz		
Memory installed	4 GB, DDR3-1333 SO-DIMM(2 x 2 GB)		
Storage			
Storage type	4 trays: 3.5-inch SATA		
Hard drives installed	4 x HDD (2 TB 5400 RPM GP) max		
Other			
Graphics	Graphics memory controller integrated in the Intel Atom D525 processor (not used)		
Network	1 x 1 GbERJ45 port		
System status			

DIVARIP2000 family comes fully loaded and fully functional with Microsoft Operating System and Bosch application pre-installed: Windows Storage Server 2008 R2, 64-bit;  ${\bf Bosch\ Video\ Recording\ Manager\ including\ Video\ Streaming\ Gateway;}$ Dynamic Transcoding.

# Technical specifications

Bectrical	
Power supply	220 W(100/240 VAC)
Energy efficiency	Energy Star compliant power supply
Power consumption (w/o hard drives)	37 Wmax 32 Widle
Mechanical	
Formfactor	4-bay mini tower
Power supply	1 x internal power supply
USB ports	3 x USB 2.0, 2 x USB 3.0 port
Network	1 x Gigabit Ethernet LAN
Dimensions (HxWxD)	180 x 200 x 212 mm (7.09 x 7.87 x 8.35 in)
Weight	w/o HDD: 4.25 kg (9.37 lb) fully loaded: 6.75 kg (14.88 lb)
Environmental	
Operating temperature	+10 ℃to +35 ℃(+50 ℉to +95 ℉)
Non-operating temperature	-40 °Cto+70 °C(-40 °Fto+158 °F)
Operating relative humidity	8 to 90%(non-condensing)
Non-operating relative humidity	5 to 95%(non-condensing)

# Ordering information

DIVAR IP 2000, 2 x 2 TB HDD

All-in-one recording solution for network surveillance systems of up to 16 channels, 2 x 2 TB storage capacity

Order number DIP-2042EZ-2HD

DIVAR IP 2000, 4 x 2 TB HDD

All-in-one recording solution for network surveillance systems of up to 16 channels, 4 x 2 TB storage capacity

Order number DIP-2042EZ-4HD

DIVAR IP 2000, w/o HDD

All-in-one recording solution for network surveillance systems of up to 16 channels, w/o HDD Order number DIP-2040EZ-00N

Accessories

DIVAR IP 2000/3000 Storage Expansion 2 TB 2 TB HDD

Order number DIP-2302-HDD

#### Represented by:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: +31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:
Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:
Robert Bosch Ltda Security Systems Division
Via Ahhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
Iatam.boschsecurity@bosch.com
www.boschsecurity.com